



Version

x-HIPRO 232 E-6

M _{dyn}		184 390 ft-lbs
Lifting capacity	ft-lbs	128 140
Lifting capacity	ft-lbs	128 096' 8"
Lifting capacity (ADC)	ft-lbs	140 590
Lifting capacity (ADC)	ft-lbs	140 537' 6"
Outreach - lifting capacity, standard	ft-lbs.	11' 10" - 11 900
		16' 1" - 8 710
		22' 0" - 5 950
		28' 3" - 4 410
		34' 9" - 3 350
		41' 8" - 2 690
		48' 11" - 2 250
	56' 5" - 1 920	
Outreach - lifting capacity, manual extensions	ft-lbs.	62' 4" - 930
Hydraulic outreach, standard	ft	56' 10"
Hydraulic boom extension	ft	40' 8" ft
Outreach, manual extensions	ft	62' 8"
Lifting height above installation level, hydr/man	ft	65' 0" / 70' 10"
Rec. oil flow	gallon/min	24 - 32
Power needed at rec. oil flow V80	hp	-
Power needed at rec. oil flow V91	hp	-
Working pressure	psi	5 000
Oil in tank	gallon	24 - 53
Tank capacity	gallon	0 - 62
Slewing angle	°	415
Max slope viable at full capacity	°	5
Slewing torque, gross	ft-lbs	20 873' 0"
Slewing speed 80	°/s	16
Slewing speed	°/s	16
Lifting speed at standard hydraulic outreach	ft/s	9' 6"
Height in folded position	"	89
Width in folded position	"	98
Install space required. Rotation area not included	"	54
Install space required with hose and pipe kit	"	54
Weight		
Crane in standard version without support legs	lbs.	5 680
Top seat	lbs.	0
Frame attachments	lbs.	90 - 140
Support leg equipment	lbs.	600 - 940

Data sheet

x-HIPRO 232 E-6