



# THE GALFAB ADVANTAGE



## Outboard Supported Side Rollers

Greasable Roller shaft is removable with two bolts for ease of replacement and maintenance.



## Container Long Sill Support Rails

Rails aid in loading misaligned containers and give added support to the long sills increasing the life of your container.



## Autofold DOT Bumpers

Bumper folds forward reducing the chance of bending and hang-ups in the landfill.



## Rear Ground Roller Cover

Standard on all Outside Rail Hoists making it easier to load and unload containers.

# STANDARD FEATURES

- 8" x 4 x 1/2" Main Frame Tube
- 3" x 2" x 1/4" Subframe
- 2 1/2" Diameter Rear Hinge
- All Working Points Greaseable
- Pintle Ready Apron
- Auto Fold Forward DOT Bumper
- 1" Spring Loaded Container Locks
- 2 1/2" Diameter Lift Cylinder Shafts
- Interchangeable 10" Vertical and Horizontal Sheaves
- 3/8 inch x 3-inch Winch Cylinder Rod Covers
- 6 Inboard and Outboard Supported Outside Rollers
- Container Long Sill Supports on Rear of Hoist Mainframe
- 48 Gallon Oil Reservoir with Sight and Temperature Gauge
- 25 Micron Filtration
- Inside and Outside Controls
- LED Lighting System
- Choice of Forward or Reverse Mount Single-Stage or Telescopic Lift Cylinders
- 7/8" Cable with Heavy Duty Swivel Eye Hook
- Galfab Auto-fold DOT Bumper
- 48-Degree Dump Angle on all Models
- 2 Minute Loading Cycle Time\* Keeping your Drivers on the Road
- Hoist Up Alarm
- Backup Alarm

# OPTIONAL FEATURES

- Behind Cab and Oversize Oil Tanks
- Tool Boxes
- Auxiliary Stops
- Poly or Steel Fenders
- Aluminum Fenders
- Tarping Systems
- "The Hooker" Hold On System
- Ratchet Tie Down Straps
- Pintle Hook
- Front Mount Pump
- PTO
- Drop Shaft
- On Board Scale Systems
- Work Lights
- Rear View Camera Systems
- Integrated hydraulics can be used, if hydraulic tarping is used



**"The Hooker"**  
Container Securement  
System



**Auxillary fold down  
stops**



**Hydraulic Reservoirs**



**Tool Boxes**



**Poly, Steel & Aluminum  
Fenders**

Shop all replacement parts at:

**Galfab.com**



# OR SERIES MODELS

Model	Capacity	CA	CA with tarp	Length	Dump Angle	Up (sec)*	Down (sec)*	On (sec)*	Off (sec)*	Lift Cylinder	Winch Cylinder	Container Length ft	Apx Weight lbs
OR60174S072	60,000	174"	186"	23'3"	48°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR60174S072R	60,000	174"	186"	23'3"	48°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR60174T121	60,000	174"	186"	23'3"	48°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7225
OR75174S072F7	75,000	174"	186"	23'3"	48°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR75174S072R7	75,000	174"	186"	23'3"	48°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR75174T121	75,000	174"	186"	23'3"	48°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7350
OR60194S072	60,000	194"	206"	24'11"	48°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR60194S072R	60,000	194"	206"	24'11"	48°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR60194T121	60,000	194"	206"	24'11"	48°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8075
OR75194S072F7	75,000	194"	206"	24'11"	48°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR75194S072R7	75,000	194"	206"	24'11"	48°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR75194T121	75,000	194"	206"	24'11"	48°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8075

\* Cycle Times are Factory developed and controlled by PTO output, oil viscosity, human and mechanical efficiency, and may vary accordingly.

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse, or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

